



The SL-700 -

The cheap power supply for price conscious costumers

Mostly used in standard PCs or as a exchange power supply the **SL-700** have thousands of satisfied customer.

Equipped with 4x S-ATA, 2x PCI-Express, 20+4 and P4 connectors they suit perfect to every home and office system. And a super silent fan guarantees a noiseless working.

Specification

Output	700W
Main board 20+4Pin (max. cable length)	1x (38cm)
4Pin/ 4+4Pin/ 8Pin 12V (max. cable length)	-/•/- (-/38cm/-)
PCI-Express 6+2Pin (max. cable length)	2x (41cm)
PCI-Express 6Pin (max. cable length)	-
IDE 4Pin (max. cable length)	3x (70cm)
S-ATA (max. cable length)	4x (54cm)
Floppy (max. cable length)	2x (84cm)
Fan Monitoring (max. cable length)	-
Fan Dimensions	120mm
Cable Management	-
ATX-Standard	ATX 2.2
PFC	Active
Noise Level	19-25dB
115/230V Input	•/•
Fan Control	auto.
Guarantee and Verification	24 months guarantee
Article number	88882052
EAN-Code	42601331122307
PSU Dimensions (H/W/D)	86/150/140mm
Package Dimensions (H/W/D)	200/200/95mm
Weight (net)	1.6Kg
Weight (gross)	1.98Kg
Packing Units (VE/VPE/PAL)	1/10/280
80+ Certificate	-

• = existing
- = non existing

Certification:



AC Input		230V 3/6A 47-63Hz					
DC Output		3.3V	5V	12V1	12V2	-12V	5Vsb
SL-700	Max. current	28A	28A	25A	25A	0.8A	2.5A
	Max. combined power	180W		500W			
		700W					